

SBP horizontal stack delivery

	SBP 46	SBP 66	SBP 86	SBP 112
Control system	MCT DCT 500	MCT DCT 500	MCT	DCT 2000
Max. sheet size, width × length cm (in)	46 × 30 (18.11 × 11.81)	66 × 30 (25.98 × 11.81)	86 × 30 (33.86 × 11.81)	112 × 30 (44.09 × 11.81)
Min. sheet size, width × length cm (in)	12 × 10 (4.72 × 3.94)	12 × 10 (4.72 × 3.94)	12 × 10 (4.72 × 3.94)	12 × 10 (4.72 × 3.94)
Max. product thickness mm (in)	4 (0.16)	4 (0.16)	4 (0.16)	4 (0.16)
Max. pile height cm (in)	80 (31.50)	80 (31.50)	80 (31.50)	80 (31.50)
Pressure N	8,000	8,000	8,000	8,000
Multiple-ups (standard/max.)	1/2	2/3	3/4	3/4
Multiple-ups (standard/max.) with optional thickness measure- ment and pile stop reset	2/3	3/4	3/5	
Infeed height cm (in)	36–96 (14.17–37.80)	36–96 (14.17–37.80)	36–96 (14.17–37.80)	36–96 (14.17–37.80)
Power consumption kVA				
3 × 400 V, 50/60 Hz	2.0	2.0	2.0	2.0
3 × 230 V, 50/60 Hz	2.0	2.0	2.0	2.0