

KR535

Tabbing System

Makes the tabbing of paper products faster and easier than ever.

PERFORMANCE

Just like other KR equipment, the KR535 performs day in and day out. Production rates in excess of 40k tabs per hour combined with a roll capacity of nearly 50k tabs makes the KR535 another real deal - productive, reliable and simple to operate. The KR535 is engineered to perform with less operator training and setup time.

VERSATILITY

All major types of tabs as well as pressure sensitive stamps and labels of various shapes and sizes can be placed on a wide assortment of products. Right or left edge tabbing, bump turn attachments, wide label kits and a folder interface conveyor option makes the KR535 a truly flexible system that can grow with your business.

VALUE

World-class manufacturing systems are used to help keep costs low. This means you get more for your dollar with KR tabbing systems. No other tabbing system matches the performance, versatility and ease of use of a KR535. Realize a profit and performance edge with the KR535.

**KR535,
Kirk-Rudy's
top selling
Tabbing System.**



RUGGED CONSTRUCTION

World-class manufacturing systems are used to help keep costs low. This means you get more for your dollar with KR tabbing systems. No other tabbing system matches the performance, versatility and ease of use of a KR535. Realize a profit and performance edge with the KR535.



KR535

Tabbing System

**General Specifications

Physical	English	Metric
Length	50"	127 cm
Width	26"	66 cm
Height	70"	178 cm
Tabletop height	33"	84 cm
Crated Weight	800 lbs	363 kg

Electrical Requirements

Voltage	Amps	Hz
120 VAC	15	20/30

Maximum Operating Speeds

Single Tabbing	30,000 pieces / hour
Double Tabbing	30,000 pieces / hour

Note: Speeds are dependent on material being fed.

**Tab Head Specifications

Physical	English	Metric
Length	29"	74 cm
Width	36.5"	93 cm
Height	14"	35 cm
Crated Weight	120 lbs	54 kg

Material Handling

Tabs	Labels
Minimum: .75 round	Minimum: .38"W x.75"L
Maximum: 2.0 round	Maximum: 3"W x 2"L STD

**Tab Base Specifications

Physical	English	Metric
Length	50"	113 cm
Width	33"	84 cm
Height	26"	66 cm
Crated Weight	780 lbs	350 kg


Material Handling

Min Stock Size	Max Stock Size	Thickness
3' x 5'	13" W x 14"L (labeling only) 11"W x 14"L (tabbing/ labeling)	Single sheet up to .18" (.62" labeling only)

You can count on years of dependable service from your KR535.



A straightforward operator interface simplifies operator training and setup.



Run 3" wide labels on the standard KR535. Even wider labels are possible using the optional 5" wide label kit.

Options

5" base height adjustment (Hydra-lift)
Narrow (1.25") product handling
5" wide label kit
Fan-fold label kit
Magnetized label kits

**Specifications subject to change without notice. Guards have been removed for clarity. Do not operate machine without guards in place.