

# D&K Auto-Kote



The affordable, state-of-the-art Auto-Kote laminator provides industrial users with a durable, versatile, cost-effective stand alone unit or the central part to a complete laminating system.

## Hot Rollers

The patented rotary heating process – heated rollers instead of the traditional heat shoe – offers users a very important option: The ability to run polypropylene as well as polyester film. Polypropylene is more cost-effective than polyester, and offers exceptional clarity, giving sheets a glossy, “wet-look” finish.

## Smooth Operator

Most important, since the Auto-Kote is not a heat shoe machine, the film doesn't get scratched and scuffed from being dragged across the stationary heat shoe. Instead, the Auto-Kote's heated roller moves with the film, applying it in an extremely relaxed manner, virtually eliminating any scuffing or scratching.

The Auto-Kote is ideal as a stand-alone laminator, or, add an automatic feeder/automatic cutter, and you can have a completely automated two-side laminating system – very economically!



Auto-Kote

# Auto-Kote Specifications

## Equipment Specifications

Dimensions:	38" W x 24" L
Electric:	220V, Single-phase, 30A
Air:	1 cfm, 1/2hp, 100 psi w/ storage tank
Weight:	200 lbs.
Temp Range:	0° - 300° F
Running Temp:	240° - 260° F
Speed:	35 ft/minute with 1.5 mil film
Min. Sheet Size:	8-1/2" x 11"
Max. Sheet Size:	27" W x Handfed or Web
Min. Sheet Thickness:	80 lb. Offset
Max. Sheet Thickness:	18 pt. Board

Engineered to meet today's rigorous laminating standards



**D&K Custom Machine Design** ■ 1795 Commerce Drive ■ Elk Grove Village, Illinois 60007-1217  
Toll-Free: 800-632-2314 ■ Illinois Phone: 847-956-0160 ■ Fax: 847-956-8214