

## VFZ 52 and VF 66 four-directional knife folding units

|                                      | <b>VFZ 52</b>  | <b>VF 66</b>  |
|--------------------------------------|--|---|
| <b>Control system</b>                | <b>MCT, DCT 2000, DCT 500</b><br><b>Rotating knife</b> | <b>MCT, DCT 2000</b><br><b>Option: Slitter shafts</b> |
| Max. size,<br>width × length cm (in) | 52 × 36<br>(20.47 × 14.17)                             | 66 × 56<br>(25.98 × 22.04)                            |
| Min. size,<br>width × length cm (in) | 12 × 10<br>(4.72 × 3.94)                               | 15 × 10<br>(5.91 × 3.94)                              |
| Max. speed m/min (ft/min)            | 160 (524.93)   | 180 (590.55)  |
| Min. speed m/min (ft/min)            | 25 (82.02)   | 25 (82.02)  |
| Max. cycling rate cycles/h           | 30,000   | 30,000  |
| Infeed height cm (in)                | 51.5–91.5 (20.28–36.02)                                | 50–95 (19.68–37.40)                                   |
| Power consumption kVA                |  |   |
| 3 × 400 V, 50/60 Hz                  | 0.8  | 0.8   |
| 3 × 230 V, 50/60 Hz                  | 0.8  | 0.8   |

Technical data can vary according to machine configuration, job, format, ink, printing stock and, possibly, other factors.