


Merit S


the three-knife trimmer with exclusive shear cutting action



## Merit S Three-knife Trimmer

Specifications

Mechanical	1000 to 4000 cycles per hour
speed	
Speed of infeed	max. 7500 cycles per hour
conveyor	
Sizes	10




	untrimm	ed (standard)	max, 384 mm 15 1.8" (A. D. E.	х 3	20 m	ım	12.5/8" (B+F)
			min, 140 mm 5 (2° (A) D(E)	X	73 m	ım	2.7/8" (B+F)
	Large size	(option)	max, 445 mm (7 F2" (A-D-E	x 3	20 m	m	12 5/8" (B+F)
	Small size	2 (uption)	min. 104 mm 4 (8*(A-0+E)	X	73 n	m	2.7/8" (B+F)
	trimmed	(standard)	max. 304 mm (21(A)	x 3	10 m	m	12 N16" (B)
			min. 136 mm 5 3/8" (A)	Х	70 m	ım	2.3/4" (B)
	Large size (option)		max. 434 mm 17" (A)	x 3	10 m	m	12.3/16" (B)
	Small size	2 (opnon)	min. 100 mm 4" (A)	X	70 m	ım	2 3/4" (B)
	Book thic	kness	max. 80 mm 3 (8°(c)				
			min. 2 mm 1360(C)				
	Trim	Front	max. 40 mm (9/16"(Γ)				
			min. 3 mm 1/8" (F)				
		Head Foot	max. 40 mm (916° (E/D)				
			min. 2 mm 1/(6" (E/D)				
Power requirements	7 kW/50 Hz, 11 kW/60 Hz						
Air requirements	40 m³/h at 6 bar (23 cfm at 87 psi)						
Weight	3500 kg (7,700 lbs.)				i i		


#### Size ranges of the cutting table cassettes

Formatausrüstung	Cassette number	Size range
Small sizes (option)	Ĭ	100 to 112 mm
	2	112 to 124 mm
	3	124 to 136 mm
Standard sizes	4	136 to 148 mm
	5	148 to 160 mm
	6	160 to 172 mm
	7	172 to 184 mm
	8	184 to 196 mm
	9	196 to 208 mm
	10	208 to 220 mm
	11	220 to 232 mm
	12	232 to 244 mm
	1.3	244 to 256 mm
	14	256 to 268 mm
	15	268 to 280 mm
	16	280 to 292 mm
	17	292 to 304 mm
Large sizes > A4 (optional)	18	304 to 316 mm
	19	316 to 328 mm
	20	328 to 340 mm
	21	340 to 352 mm
	22	352 to 364 mm
	2.3	364 to 376 mm
	24	376 to 388 mm
	25	388 to 400 mm
	26	400 to 412 mm
	27	412 to 424 mm
	28	424 to 434 mm

Other sizes on request.

Design, measurements and specifications subject to change.





#### MÜLLER MARTINI

#### Müller Martini Marketing AG

Untere Bruhlstrasse 13 CH-4800 Zoffingen, Switzerland Plume —41-62-765-45-75 Fax —41-62-751-55-50

# Merit S Three-knife Trimmer – the ideal combination of superior trim quality and production flexibility

### Fast set-up

The product mix processed by mid-size operations has become more diversified. Therefore, machines with very short makeready are needed to

compete in today's market. The Müller Martini Merit S Three-knife Trimmer, with automatic makeready system, ideally meets these requirements.

## Processing of a wide range of products

The large size range and trim capacity allows the Merit S Three-knife Trimmer to efficiently handle a wide variety of perfect bound and thread sewn books.


## Processing of book blocks for case-binding

The Merit S handles the most demanding needs with ease (trim thickness, cycle time, single or collect trimming).

### • Operation and maintenance The Müller Martini sales and service network ensures support and a true partnership with users around the world.










Delivery




Automatic makeready and control system

The Müller Martini Merit S Three-knife Trimmer is the key to versatility and profitable production in the bindery.



#### Infeed conveyor

Greater infeed flexibility is a critical advantage for efficient production. Books enter the three-knife trimmer from the left or right, individually or in multiples. Thin products are handled gently and size settings of the hopper and knife station are automated.




## Book infeed into the knife station

Positively controlled infeed is a critical requirement for precise trimming.

The products enter the knife station spine leading, thereby preventing curl-up of the endsheets or covers.

Books gently decelerate as they approach the front stops (to avoid bounce) and are accurately aligned prior to clamping.



#### Knife station

High trim quality is assured by the proper trim sequence. Face, head and foot are trimmed in one station. Books are pressed over their full area and clamp pressure is pneumatically adjustable. Trimming is done against plastic cutting sticks.

Shear cutting action for head and foot trim is towards the spine to prevent tear-outs. For trim removal, the trimmer can be hooked up to an exhaust system or optional conveyor.




#### Book delivery

Gentle handling of the trimmed books guarantees top trim quality and reliable downstream finishing. The delivery system ensures positive control without marking.

#### Automatic makeready and control system

The interactive PLC provides convenient operation. It automatically sets up basic data for the book (size, speed, and clamp pressure). Subsequent orders can be pre-programmed and saved while pro-




duction is running.

Motorized adjustments
for size changes are made
automatically after removal of the cutting table.
Fine adjustments can be
made on-the-fly.
The Merit S uses the
same control system as
the Müller Martini
Zenith S Three-knife
Trimmer.

#### Shear cutting action

Shear action trimming of the Merit S ensures superior quality and a clean cut. Trim quality is an important visual aspect of the printed product.



## Merit S,

the three-knife trimmer with exclusive shear cutting action

This brochure may show components which are not standard equipment and are available as options only.

In some cases protective covers have been removed or opened for illustrative purposes. They must be in place during machine operation.

Design, measurements and specifications are subject to change.

MÜLLER MARTINI

#### Müller Martini Marketing AG

Untere Brühlstrasse 13 CH-4800 Zofingen, Switzerland Phone ++41-62/745 45 75 Fax ++41-62/781 55 50