



 = position perfect binder

	Electrical data:
<p>Electrical data for service voltage 220V/60Hz The cross section of the protective conductor matches the cross section of the line conductor, the minimum cross section of the protective conductor is 10mm² (0,0155 square inch).</p>	
<p>① 3260000 800000 9100000 S = 28 kVA I = 75 A φ = 3x80 A</p>	

	Air requirement:
<p>Compressed air has to comply with DIN ISO 8573-1, dust : class 1 water: class 4 oil : class 2</p>	
<p>D+ H= 1000 dm³/min ; 6 bar pressure</p>	

- 326... perfect binder Quickbinder
- 800... transport-system (12m)
- 910... three-knife trimmer 60e

26.02.2018

Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of an utility model or design.

Colour: Traffic blue RAL 5017 and light grey RAL 7035.

Maple Press, USA				CAD	Datum	Name	Maßstab	Angebots Nr.	Auftrags Nr.		
				Gez.	22.02.18	Gaertner	1:100		493497		
				Gepr.					493498		
1	18-000008	22.02.18	Gaertner	wohlenberg				Ident.-Nr.	Version	Seite	Format
				Buchbindesysteme GmbH				6305305	1	1	A3
Vers.	Änderung	Datum	Name								