



| | RLA-2 | RLA-3 | RLA-4 | RLA-6 | RLA-7 | RLA-7B |
|---|-------|-------|-------|-------|-------|--------|
| A | 87 | 113 | 120 | 148 | 165 | 165 |
| B | 97 | 112 | 122 | 139 | 147 | 157 |
| C | 134 | 160 | 167 | 195 | 212 | 212 |
| D | 108 | 134 | 141 | 169 | 186 | 186 |
| E | 66 | 80 | 90 | 107 | 115 | 125 |

working height: stepless adjustable 86-98cm



automatic jogger RLA with air removal roller

| Typ | usable size | width of air-removal roller |
|--------|--------------|-----------------------------|
| RLA-2 | 66 x 108 cm | 81 cm |
| RLA-3 | 80 x 134 cm | 106 cm |
| RLA-4 | 90 x 141 cm | 114 cm |
| RLA-6 | 107 x 169 cm | 141 cm |
| RLA-7 | 115 x 186 cm | 158 cm |
| RLA-7B | 125 x 186 cm | 158 cm |

| | RLA-2 RLA-2-P | RLA-3 RLA-3-P | RLA-4 RLA-4-P | RLA-6 RLA-6-P | RLA-7 RLA-7-P | RLA-7B RLA-7B-P |
|--|------------------|------------------|------------------|------------------|------------------|--------------------|
| usable size cm | 66 x 108 | 80 x 134 | 90 x 141 | 107 x 169 | 115 x 186 | 125 x 186 |
| space required cm | 120 x 144 | 137 x 170 | 147 x 177 | 159 x 205 | 167 x 222 | 177 x 222 |
| max. stackheight cm | 16,5 | 16,5 | 16,5 | 16,5 | 16,5 | 16,5 |
| electr. power 50/60 Hz kW | 1,75 / 2,2 | 1,75 / 2,2 | 1,75 / 2,2 | 2,3 / 2,45 | 2,3 / 2,45 | 2,3 / 2,45 |
| blower l/min | 800 | 800 | 800 | 1200 | 1200 | 1200 |
| required compr. air l/min. bei 6-8 bar | 12 | 12 | 12 | 15 | 15 | 15 |
| weight kg | 500 | 540 | 540 | 690 | 730 | 750 |
| power supply V | 220 - 415 | 220 - 415 | 220 - 415 | 220 - 415 | 220 - 415 | 220 - 415 |
| | 50/60 Hz | 50/60 Hz | 50/60 Hz | 50/60 Hz | 50/60 Hz | 50/60 Hz |

- table surface in stainless steel with air nozzles
- manual sideflaps with air nozzles right and left (opt. pneum. RLA-...-P)
- set of laymarks
- air-removal roller frequency controlled
- jogging motor frequency controlled
- rotation direction right and left switchable



machine freestanding. Exact alignment allows better cutting tolerances and higher output at the cutting machine. Comfortable operation by footpedal. Jogging intensity stepless adjustable at the control panel. Jogging to the right and left side possible. The operator can choose operation with and without air for easier transport of materials.

Air-removal roller with stepless adjustable roller speed and stepless adjustable roller pressure.

Balancer shaft for exact equal air-removing of different paper sizes. Air-removing operation one or two times with different roller pressures. Safety light barriers in front of the working area to ensure that there is no unallowed action of the operator while the machine is moving.

Jogger can also be connected to a gripper system as an option.